

ChM produces and distributes advanced medical solutions in 3 main divisions:



Comprehensive portfolio of products for traumatology, including systems designed for fractures fixation and deformities correction of extremities and pelvis.



Wide range of advanced solutions for cervical and thoraco-lumbar stabilization of spine, including pedicle screw systems for open and MIS procedures, various interbody devices and fixation plates.



Instruments and implants for cranio-maxillofacial surgeries, dedicated for fracture fixations, reconstructions, distractions and orthognathic surgeries.

## WRIST ARTHRODESIS PLATES

3.7206.xxx



To bring medical solutions

Document No B/P-06  
Review date P-001-04.08.2020

[www.chm.eu](http://www.chm.eu)



## WRIST ARTHRODESIS PLATES



# WRIST ARTHRODESIS PLATES

## Design aligned with anatomy

- optimized anatomical profile
- fit to a wide range of anatomies
- facilitated anatomical reduction
- no radius impingement

## Multiple plate options

- system consists of 2 types of plates:
  - 6-hole plate with 14mm diameter
  - 12-hole plate with 21mm diameter
- provided 4 corner, 3 corner and other wrist fusions fixation

## Concave profile

- facilitated plate positioning
- minimal bone removal
- no intraoperative tilting of the plate

## Chamfered plate borders

- minimized soft-tissue irritation

## Double screw row in 12-hole plate

- second row for additional stabilization and complete fixation

## Reamers

- dedicated for plate size
- recess matches exactly the plate profile
- reduced amount of removed bone
- cannulation for easier handling

## Locking hole design

- the screws heads do not protrude above the surface of the plate what significantly reduces tissue irritation
- increased strength of the screw-to-plate threaded connection

## K-wire holes

- provisional plate positioning

## Multiple screw options

- locking and VA locking screw gives multiple configuration for individual cases

## Variable-Angle screws

- high strength cobalt alloy material
- compatible with all locking holes
- 30° angulation cone
- VA screw re-lock possibility

